


QUARTZ 7000 DIESEL 10W-40



New '2008' reinforced formulation for **QUARTZ 7000 10W-40**, synthetic based engine oil. The nature of the used lubricant bases coupled with a specific additivation give to this oil some great qualities.

USES

- **TOTAL QUARTZ DIESEL 7000 10W-40** has been developed to cover the requirements of **diesel engines** (passenger cars and light industrial vehicles).
- **TOTAL QUARTZ DIESEL 7000 10W-40** is perfectly suited to **turbo-charged and multi-valved engines**.
- **TOTAL QUARTZ DIESEL 7000 10W-40** is perfectly suited to **normal driving conditions (few use in town)**
- **TOTAL QUARTZ DIESEL 7000 10W-40** is perfectly adapted to vehicles equipped with **catalysts** and using **unleaded fuel or liquefied petroleum gas**.

PERFORMANCES

Specifications	ACEA 2007 API	A3/B4 SL/CF
OEMs	PEUGEOT CITROEN VOLKSWAGEN MB	Gasoline and diesel – PSA B712294 501.01 / 505.00 229.1

CUSTOMER BENEFITS

The **QUARTZ DIESEL 7000** technology allows:

- A good **resistance to oxidation**
- A good engine **cleanliness**
- A **Long-term wear protection** of the most sensitive parts of the engine (distribution, ring, plunger and liner)
- An Increased engine life.

CHARACTERISTICS

TOTAL QUARTZ 7000 DIESEL 10W-40	Units	SAE Grade 10W-40
Volumetric mass at 15°C	kg/m ³	873.6
Viscosity at 40°C	mm ² /s	96.8
Viscosity at 100°C	mm ² /s	14,81
Viscosity index	-	160
Flash point Cleveland	°C	232
Pour point	°C	-24°C

The typical characteristics mentioned represent mean values.

TOTAL LUBRIFIANTS
16, rue de la République
92800 PUTEAUX
1/1

QUARTZ 7000 DIESEL 10W-40
Sheet updated : 03/08
Sticker reference: MPC /03/07



This lubricant, when used in accordance with our recommendations and for the application for which it is intended, does not constitute a special hazard
A safety data file conforming to the requirements of current EC legislation is available from your local trade consultant